

VG.CF22 flat suction cups, NBR-HNBR, with reinforcements

- Ideal for handling plastic parts and dry sheet metal
- Suitable for items with flat surfaces
- Suitable for handling items with lifting force parallel to the surface thanks to the reinforcements that increase friction and prevent deformations
- The HNBR version enables to work at high temperatures, whereas silicone or other mixtures may release traces of material
- The HNBR compound is robust and wear resistant, suitable for the removal of hot plastic parts from the relevant moulds
- HNBR and NBR compounds are ideal for applications where contamination of the material must be avoided (PWIS)



Application example



Technical data


Material	Lifting force [N] perpendicular to the surface, at various vacuum levels			Lifting force [N] parallel to the surface, at various vacuum levels			Volume	Min curve radius	Max vertical movement	Suction cup weight
	-20 kPa	-60 kPa	-90 kPa	-20 kPa	-60 kPa	-90 kPa	[cm³]	[mm]	[mm]	[g]
NBR 60	6.1	13.7	18.7	5.1	8.2	8.5	1	18	1.5	1.3
HNBR 60	6.1	13.7	18.7	5.1	8.2	8.5	1	18	1.5	1.1

Technical features


Material	Colour	Hardness	Temperature range
NBR	Black	60 Shore	-30 ÷ +100 °C
HNBR	Blue	60 Shore	-25 ÷ +150 °C

Identification codes			
Drawing	Alphanumeric code	Suction cups with fitting	Order code
A	VG.CF22N.60.M5F	VG.CF22 suction cup, NBR, 60 Shore, M5 female	2321970
B	VG.CF22N.60.G18M	VG.CF22 suction cup, NBR, 60 Shore, G1/8" male	2321972
C	VG.CF22N.60.G18MF	VG.CF22 suction cup, NBR, 60 Shore, G1/8" male/M5 female	2321973
D	VG.CF22N.60.G18MFV	VG.CF22 suction cup, NBR, 60 Shore, G1/8" male/M5 female with 0.6 mm calibrated hole	2321974
A	VG.CF22H.60.M5F	VG.CF22 suction cup, HNBR, 60 Shore, M5 female	2322012
B	VG.CF22H.60.G18M	VG.CF22 suction cup, HNBR, 60 Shore, G1/8" male	2322014
C	VG.CF22H.60.G18MF	VG.CF22 suction cup, HNBR, 60 Shore, G1/8" male/M5 female	2322015
D	VG.CF22H.60.G18MFV	VG.CF22 suction cup, HNBR, 60 Shore, G1/8" male/M5 female with 0.6 mm calibrated hole	2322016


A




B



C




D




Identification codes			
Drawing	Alphanumeric code	Suction cups	Order code
A	VG.CF22N.60	VG.CF22 suction cup, NBR, 60 Shore	2321971
A	VG.CF22H.60	VG.CF22 suction cup, HNBR, 60 Shore	2322013

A




Identification codes			
Drawing	Alphanumeric code	Fittings	Order code
A	FT.M5F	Fitting, M5 female	1700006
B	FT.G18M.17	G1/8" male fitting	1700018
C	FT.G18M.M5F	G1/8" male / M5 female fitting	1700016
D	FT.G18M.M5F.VF	G1/8" male / M5 female fitting, with 0.6 mm calibrated hole	1700017


A



B



C



D

