
VG.FP40F multi-bellows suction cups in FDA-compliant food-grade silicone

- The silicone is FDA-compliant and therefore suitable for handling unpackaged food
- Suitable for level compensation
- High vertical movement, useful for separating thin parts



Application example



Technical data


Material	Lifting force [N] perpendicular to the surface, at various vacuum levels			Lifting force [N] parallel to the surface, at various vacuum levels			Volume	Min curve radius	Max vertical movement	Suction cup weight
	-20 kPa	-60 kPa	-90 kPa	-20 kPa	-60 kPa	-90 kPa	[cm³]	[mm]	[mm]	[g]
SIL 50 FDA	10.8	31.5	–	–	–	–	27	11	33	10

Technical features


Material	Colour	Hardness	Temperature range
Silicone, FDA SIL	Transparent	50 Shore	-70 ÷ +200 °C

Identification codes			
Drawing	Alphanumeric code	Suction cups with fitting	Order code
A	VG.FP40F.50.G18F	VG.FP40 suction cup, FDA-compliant silicone, 50 Shore, 1/8" NPSF female	2322080
B	VG.FP40F.50.G18M	VG.FP40 suction cup, FDA-compliant silicone, 50 Shore, G1/8" male	2322082
C	VG.FP40F.50.G14M	VG.FP40 suction cup, FDA-compliant silicone, 50 Shore, G1/4" male	2322083
D	VG.FP40F.50.G38M	VG.FP40 suction cup, FDA-compliant silicone, 50 Shore, G3/8" male	2322084


A




B



C




D




Identification codes			
Drawing	Alphanumeric code	Suction cups	Order code
A	VG.FP40F.50	VG.FP40 suction cup, FDA-compliant silicone, 50 Shore	2322081

A




Identification codes			
Drawing	Alphanumeric code	Fittings	Order code
A	FT.G18F.18	1/8" NPSF female fitting	1800019
B	FT.G18M.18	G1/8" male fitting	1800018
C	FT.G14M.18	G1/4" male fitting	1800014
D	FT.G38M.18	G3/8" male fitting	1800038


A




B



C



D



Identification codes		
Alphanumeric code	Disc	Order code
AC.DF40	Perforated disc for thin films, diameter 40 mm	2321755