

VG.U6S flat suction cups in FDA-compliant silicone

- Food-grade silicone compound (FDA-approved)
- Suitable for high working temperatures
- Suitable for objects with flat or slightly curved surfaces



Application example



Technical data


Material	Lifting force [N] perpendicular to the surface, at various vacuum levels			Lifting force [N] parallel to the surface, at various vacuum levels			Volume	Min curve radius	Max vert. movement	Suction cup weight
	-20 kPa	-60 kPa	-90 kPa	-20 kPa	-60 kPa	-90 kPa	[cm³]	[mm]	[mm]	[g]
SIL 50 FDA	0.5	1.5	2.5	0.5	1.3	2.2	0.05	5	0.3	0.1

Technical features


Material	Colour	Hardness	Temperature range
Silicone, SIL FDA	Red	50 Shore	-70 ÷ +200 °C

Ordering information			
Drawing	Alphanumeric code	Suction cups with fitting	Order code
A	VG.U6S.50.M3M.E5	VG.U6 suction cup, FDA-compliant silicone, 50 Shore, M3 male, 5 mm hex	2321653
B	VG.U6S.50.M5M.E8	VG.U6 suction cup, FDA-compliant silicone, 50 Shore, M5 male, 8 mm hex	2321053

A




B




Ordering information			
Drawing	Alphanumeric code	Suction cups	Order code
A	VG.U6S.50	VG.U6 suction cup, FDA-compliant silicone, 50 Shore	2321654

A



Ordering information			
Drawing	Alphanumeric code	Fittings	Order code
A	FT.M3M.E5	M3 male fitting, 5 mm hex	2321402
B	FT.M5M.E8.06	M5 male fitting, 8 mm hex	2321005

A



B

