
VG.U9F flat suction cups in FDA-compliant food-grade silicone

- Food-grade silicone compound (FDA-approved)
- Suitable for high working temperatures
- Suitable for objects with flat or slightly curved surfaces



Application example



Technical data


Material	Lifting force [N] perpendicular to the surface, at various vacuum levels			Lifting force [N] parallel to the surface, at various vacuum levels			Volume	Min curve radius	Max vert. movement	Suction cup weight
	-20 kPa	-60 kPa	-90 kPa	-20 kPa	-60 kPa	-90 kPa	[cm³]	[mm]	[mm]	[g]
SIL 50 FDA	1	2.5	3.8	1	2.5	3.5	0.1	6	0.5	0.2

Technical features

Material	Colour	Hardness	Temperature range
Silicone, FDA SIL	Transparent	50 Shore	-70 ÷ +200 °C


Ordering information			
Drawing	Alphanumeric code	Suction cups with fitting	Order code
A	VG.U9F.50.M5M.E8	VG.U9 suction cup, FDA-compliant silicone, 50 Shore, M5 male, 8 mm hex	2321403

A



Ordering information			
Drawing	Alphanumeric code	Suction cups	Order code
A	VG.U9F.50	VG.U9 suction cup, FDA-compliant silicone, 50 Shore	2321404

A



Ordering information			
Drawing	Alphanumeric code	Fittings	Order code
A	FT.M5M.E8.05	M5 male fitting, 8 mm hex	2321405

A

