PIPE THREAD COMPATIBILITY





ΑΠΤΟΜΑΤΙΟΝ











	FEMALE THREAD										
		NPT FPT FNPT NPTF	BSPP G PF RP	BSPT PT R RC JIS	JIS 30	JIC 37 DEG	SAE 37	SAE 42	SAE 45	DIN 24	DIN 60
MALE THREAD	UNI	x	x	x							
	NPT MPT MNPT NPTF	x									
	BSPP G		x								
	BSPT PT R JIS		x	x							
	JIS 30			x	x						
	JIC 37 DEG					x					
	SAE 37						x				
	SAE 42							x			
	SAE 45							х	x		
	DIN 24									x	
	DIN 60										x
		10/32 MALE WORKS WITH M5 FEMALE BUT M5 MALE DOES NOT WORK WITH 10/32 FEMALE									

UNI	UNIVERSAL THREAD CONNECTION (SEE CHART) - STRAIGHT THREAD WITH SEALING RING
NPT	AMERICAN NATIONAL TAPERED PIPE THREAD - TAPERED MALE OR FEMALE THREAD
МРТ	AMERICAN NATIONAL TAPERED PIPE THREAD - TAPERED MALE NPT THREAD
FPT	AMERICAN NATIONAL TAPERED PIPE THREAD - TAPERED FEMALE NPT THREAD
MNPT	AMERICAN NATIONAL TAPERED PIPE THREAD - TAPERED MALE NPT THREAD
FNPT	AMERICAN NATIONAL TAPERED PIPE THREAD - TAPERED FEMALE NPT THREAD
NPTF	AMERICAN NATIONAL TAPERED PIPE THREAD (FUEL/DRYSEAL) - TAPERED MALE OR FEMALE NPT FUEL/DRYSEAL THREAD
BSPP	BRITISH STANDARD PARALLEL PIPE THREAD - STRAIGHT MALE OR FEMALE THREAD
G	BRITISH STANDARD PARALLEL PIPE THREAD - STRAIGHT MALE OR FEMALE BSPP THREAD
PP	BRITISH STANDARD PARALLEL PIPE THREAD - FEMALE BSPP THREAD
BSPT	BRITISH STANDARD TAPERED PIPE THREAD - TAPERED BSPP MALE OR FEMALE THREAD
PT	BRITISH STANDARD TAPERED PIPE THREAD - TAPERED BSPP MALE OR FEMALE THREAD

R	BRITISH STANDARD TAPERED PIPE THREAD - TAPERED BSPP MALE OR FEMALE THREAD
RP	BRITISH STANDARD TAPERED PIPE THREAD - TAPERED BSPP FEMALE THREAD
PF	BRITISH STANDARD TAPERED PIPE THREAD - TAPERED BSPP MALE OR FEMALE THREAD
RC	BRITISH STANDARD TAPERED PIPE THREAD - TAPERED BSPP MALE OR FEMALE THREAD
JIS	JAPANESE INDUSTRIAL STANDARD TAPERED PIPE THREAD
JIC 37	NORTH AMERICAN FLARE - STRAIGHT THREADS, 37 DEG FLARE - MALE OR FEMALE
SAE 37	NORTH AMERICAN FLARE - STRAIGHT THREADS, 42 DEG FLARE - MALE OR FEMALE
SAE 42	NORTH AMERICAN FLARE - STRAIGHT THREADS, 42 DEG FLARE - MALE OR FEMALE
SAE 45	NORTH AMERICAN FLARE - STRAIGHT THREADS, 45 DEG FLARE - MALE OR FEMALE
DIN 24	EUROPEAN STANDARD - STRAIGHT THREADS, 24 DEG FLARE - MALE OR FEMALE
DIN 60	EUROPEAN STANDARD - STRAIGHT THREADS, 60 DEG FLARE - MALE OR FEMALE
JIS 30	JAPANESE INDUSTRIAL STANDARD PIPE THREAD - STRAIGHT THREADS, 30 DEG FLARE - MALE OR FEMALE



sales@flotronicsautomation.com

Flotronics Automation—East 10435 Ortonville Rd. I Clarkston, MI 48348 Phone: 248-625-8990 | Fax: 248-625-8818

www.flotronicsautomation.com

Flotronics Automation—West 3542 Roger B. Chaffee SE I Wyoming, MI 49548 Phone: 616-682-7013 | Fax: 248-625-8818

COMPLETE AUTOMATION SOLUTIONS



ΑΠΤΟΜΑΤΙΟΝ















KALOK®

4SSURED Ø

4UTOMATION















Did you know Flotronics Automation has a large inventory of flexible, cost effective polyurethane tubing in various sizes and colors? Try our Flo-Flex Tube today!



ANDERSON FITTINGS





FreelinWade

MENCOM

Electrical Connectors

Panasonic

MARK-PLAS

AVENTICS









Tolomatic







ini lec THE ART OF SIMPLICITY









